

Appln. No.: 09/904,468  
Amdt. dated June 13, 2003  
Reply to Office action of 02/14/03

**IN THE SPECIFICATION**

Please insert the following subheading beginning on page 2, line 1, with the following subheading:

b1 - -RELATED APPLICATION - -

Please add the following to line 2, of pg 1,

B2 --This application is a divisional of copending application Serial No.09/079,726 filed on May 15, 1998 and now United States Patent 6,294,127.

Please replace the paragraph beginning at page 6, line 1, with the following rewritten paragraph:

B3 - -In Figs. 4-6, a process of the present invention is illustrated. As shown in Fig. 4, the corner reinforcement 40 is placed in an orifice 82 of a mold 80. an inner surface 84 of the mold 80 defines an outer surface 23 of the container body 22. The corner reinforcement 40 is disposed in the mold 80?. The corner reinforcement 40 is secured in the mold 80? by inserting the pin 42 into an indexing mechanism 86. The indexing mechanism 86 includes a receiver 90 is disposed in an aperture 92 of the mold 80?. The receiver 90 includes a cylindrical portion 94 disposed in the aperture 92. The cylindrical portion 94 includes a bore 96 adapted to receive and retain the pin 42 of the corner reinforcement 40 therein. The receiver 90 further includes a base portion 98 disposed in a recess 104. The base portion 98 is laterally displaceable within the recess 104.- -